



WESSEX INTUMESCENT SUPPLIES LTD

Unit 22, Regent Trade Park, Barwell Lane, Gosport, Hants. PO13 0EQ

Fire, Draught, Weather & Acoustic Seals
Conservatory Roof Glazing Systems


Tel: 01329 221111 Fax: 01329 221122

Email: sales@wis-ltd.com

Website: www.wis-ltd.com


THRESHOLD SEALS & RAIN DEFLECTOR

TS100 LOW ACCESS THRESHOLD SEAL - for inward or outward opening doors



Weathersealing with minimum obstruction for use with inward or outward opening doors. Reduces rain, draught, snow, dust, dirt and noise. Very low profile.


Minimum disruption to foot traffic and easily negotiated with prams, wheelchairs, etc. Aluminium profile with long lasting dome seal, which engages with door bottom to create efficient sealing.



Hidden screw fixing. Suitable for domestic and commercial use. Ideal for hotels, shops, offices, sheltered housing, surgeries, schools, public buildings etc. Complies with Part M Building Regulations


Available in natural aluminium or gold finish at lengths to suit all door widths.

TS200 LOW ACCESS THRESHOLD SEAL - for inward opening doors only



Weathersealing with minimum obstruction for use with inward opening doors. Reduces rain, draught, snow, dust, dirt and noise. Very low profile.


Minimum disruption to foot traffic and easily negotiated with prams, wheelchairs, etc. Aluminium profile with long lasting seals, which engage with face & door bottom to create efficient sealing. Thermal cover available for doors with high insulation requirements.



Suitable for domestic and commercial use. Ideal for hotels, shops, offices, sheltered housing, surgeries, schools, public buildings etc. Complies with Part M Building regulations.


Available in natural aluminium or gold finish at lengths to suit all door widths.

TS300 LOW ACCESS THRESHOLD SEAL - for outward opening doors only



Weathersealing with minimum obstruction for use with outward opening doors. Reduces rain, draught, snow, dust, dirt and noise. Very low profile.


Minimum disruption to foot traffic and easily negotiated with prams, wheelchairs, etc. Aluminium profile with long lasting seal, which engage with face door to create efficient sealing.



Suitable for domestic and commercial use. Ideal for hotels, shops, offices, sheltered housing, surgeries, schools, public buildings etc. Complies with Part M Building regulations.

Available in natural aluminium or gold finish at lengths to suit all door widths.

RAIN DEFLECTOR 32 – for inward or outward opening doors



Designed to deflect water away from the door bottom, either in conjunction with a threshold sill, or to replace a weatherboard. Supplied with edge protecting end caps.

Quick and easy to fit, pre-drilled fixing holes.

Available in natural aluminium or gold finish at lengths to suit all door widths.

